

| | | |
|--------------------|------------------------|--|
| EXTERNAL FEATURES: | Brickwork: | General: Refer External Colour scheme for Brick type. Clay bricks from builder's Category 1 (BC1.06) |
| | Mortar Joints: | Off White (Joint profile Product specific) |
| | External Mouldings: | Lightweight exterior moulding with acrylic texture coating render to all exposed surfaces, render colour from builder's Category 1 (Façade specific, refer working drawing for extent of cover) |
| | Render: | Acrylic texture coating render 3 Coat System, from Builder's Category 1 (Façade specific, refer working drawing for extent) |
| | Wall Cladding Systems: | Various alternative wall cladding systems are used on a House / Product / Façade specific basis. These wall cladding systems include but are not limited to autoclaved aerated concrete panels, Fibre Cement products, and feature timber panelling (Product / Façade specific, refer working drawing for extent) |
| | Roof Cover: | Tiles: Concrete roof tiles, from Builder's Category 1 (RTC1.02) (Product specific) Metal: Colorbond Lower corrugated sheet roof, metal deck roof or tray deck and Zinalume to First floor roofs (Product specific) |
| | Roof Plumbing: | Colorbond metal fascia and barge Colorbond Quad gutter with 100 x 50mm rectangular downpipes (Product specific) Rainheads: Colorbond Metal Square Flat bottom or Half Round (Product specific) |
| | Entry Doors: | Front: Hume Newington Range 'XN1' 2040mm high x 820mm wide – Clear Glass (Product specific refer working drawings) Rear/Laundry (Hinged Door only): External flush panel door (Product specific, refer working drawings for size and location) Aluminum Clear Glazed door in Powder coated finish (Product specific, refer working drawings for size and location) |
| | Door Furniture: | Front Door: Canterbury Zenith Entry Knobset entry set with Canterbury Orbit Deadbolt Regional North and Gippsland: Lockwood Symmetry Manor Knobset entry set External Hinged Door: Canterbury Zenith Entry Knobset entry set (Product specific) Regional North and Gippsland: Lockwood Symmetry Manor Knobset entry set (Product specific) Door Stop: 75mm cushion, White |
| | Entry Frame: | Front: Timber with aluminium sill and clear glazed sidelight(s) (Product specific) Rear/Laundry (Hinged door): Timber frame with aluminium sill or aluminium frame (Product Specific, refer working drawings for size and location) Rear (Sliding door): Refer "Sliding Doors" item below (Product specific, refer working drawings for size and location) |
| | Windows: | Aluminum awning or sliding, with powdercoat finish (Product specific) Note: ** Flyscreens to all openable windows (Included) Note: Locks to all openable windows (Not Included) |
| | Sliding Doors: | Aluminum, powdercoat finish (Product specific, refer working drawings) Note: Flyscreens to Sliding Doors (Not Included) |
| | Infills Over Windows: | Single Storey: Brick infills, Rendered Hebel® aerated concrete infills, Lightweight Cladding infills (Product specific, refer working drawings for type/extent) Double Storey: Brick infills, Rendered Hebel® aerated concrete infills, Lightweight Cladding infills. (Product specific, refer working drawings for type/extent) |
| | ** Window Coverings: | Living & Bedrooms: Sheer roller blinds to Living areas & roller blackout blinds to Bedrooms (Refer Internal Colour Scheme for finish) |
| | Balcony Balustrade: | Product Specific (refer working drawings for design, size and location) |

| | | |
|---------------------|--------------------------|---|
| FRAMING: | Walls: | Single Storey: 90mm thick stabilised timber frame throughout Double Storey: 90mm thick stabilised timber frame throughout to both floors Boundary/Party wall: Hebel system, timber fireproof and acoustic system to BCA Requirements |
| | Roof: | Stabilised timber roof trusses |
| INSULATION: | Ceiling: | R4.0 Glasswool batts; excludes Garage, Outdoor Room/Verandah and Portico and First Floor floor system areas |
| | First Floor Joists Area: | R4.0 Glasswool batts; to floor area above Garage, Outdoor Room/Verandah and Portico ONLY. |
| | External walls: | R2.0 Glasswool batts, including party wall between house and garage. No insulation to garage walls |
| SISALATION: | Weather Wrap: | Medium Duty to ground and first floor external walls; joins in weather wrap to be taped and gaps around windows/doors sealed. |
| HOT WATER SERVICE: | ** Electric: | Electric 170Ltr heat pump water heater system |
| SUSTAINABLE ENERGY: | ** Energy Monitoring: | Wiser energy gateway module, including power tag to mains, solar and selected circuits. |
| | ** PV Solar Panels: | PV solar panels 4KW with standard invertor and PV solar modbus |
| | ** Recycled Water: | Recycled water to toilets, laundry and one external tap |
| | Draft Exclusion: | Exhaust Fans: Backdraft shutter incorporated in exhaust fan vented to external air Entry frames: Full perimeter draft seals to all entry door frames and internal access door to garage but excluding garage external pedestrian door. |
| | | |
| PAINTWORK: | General: | Dulux paints to be used throughout in accordance with Paint Specification 20 Refer Internal Colour scheme for paint colours. |
| | External: | Front door: Sealer undercoat with enamel gloss top coats Other Hinged Doors: Sealer undercoat with Low Sheen acrylic top coats Fascia, gutter & downpipes: Colorbond (Maximum two colours) Woodwork: Low Sheen acrylic (one colour) |
| | Internal: | Woodwork and Doors: Sealer undercoat with enamel gloss top coats (Doors, skirting and architraves to be one colour) Ceilings: Flat acrylic (one colour throughout) Walls: Sealer undercoat and two top coats washable matt acrylic (one colour throughout) |
| INTERNAL FEATURES: | Ceiling Height: | Single Storey: 2400mm throughout Double Storey: ** 2550mm main living floor level, 2400mm to all other floors (Product specific) |
| | Room Doors: | Flush panel 2040mm high |
| | Room Door Furniture: | Lever handles as Builder's Category 1 Note: Privacy lever set to Powder room and Bathroom |
| | Door Stop: | 75mm White cushion stop |
| | Mouldings: | Skirtings: 67mm high double pencil round PMDF. Architraves: 42mm wide double pencil round PMDF. |
| | Cornice: | 75mm Cove (Tru Scotia) cornice throughout |

| | | |
|---|----------------------|--|
| APPLIANCES: | Underbench Oven: | Inalto IO64M.1, stainless steel/glass, electric, 600mm wide, fan forced (2051312) |
| | Cook Top: | ** Inalto ICI604TB, stainless steel, electric induction cooktop, 600mm wide, |
| | Dishwasher: | ** Inalto IDW7S freestanding, stainless Steel 600mm wide (2049882) |
| | Rangehood: | InAlto IUM52 Undermount rangehood stainless steel, 52cm wide (2047338) – ducted through to external air |
| KITCHEN: | Sink: | Franke SKX621 1160 Double bowl stainless steel with one tap hole |
| | Tap: | Mizu Drift SQ rectangular sink mixer with lever handle, chrome finish |
| | Microwave Provision: | 600w x 450h incorporated in kitchen base cupboards and vented into adjacent cupboard space, including single power point. (Not included in all products, refer working drawings for standard inclusion) |
| | Cabinetry: | <div><div>General:</div><div>Base Cupboards:</div><div>Overhead Cupboards:</div><div>Doors/Drawers:</div><div>Bench Tops (Kitchen):</div><div>Bench Top Edges (Kitchen):</div><div>Handles:</div></div> <div>Refer Internal Colour scheme for finish Fully lined modular cabinets (Refer working drawings for layout and extent) Fully lined modular cabinets (Refer working drawings for layout and extent) Standard laminate, from builder's Category 1 ** 20mm thick stone composite benchtop. Select from builder's Category 1 range Laminated square edge From builder's Category 1 (Refer Colour scheme)</div> |
| BATHROOM/ ENSUITE OR POWDER ROOM: | Mirrors: | Silver backed with polished edges, seated on vanity, to full width of vanity |
| | Basins: | <div><div>Inset Basin:</div><div>Semi Recessed Basin:</div><div>Wall Basin:</div></div> <div>Kado Arc Square white vitreous china inset basin with chrome pop-up waste (Product specific) Kado Arc Square white vitreous china basin with chrome pop-up waste (Product specific) Posh Solus Mini wall basin (1 tap hole) with Mizu 40mm round chrome bottle trap and chrome pop-up waste. (not included in all products, refer working drawings for standard inclusion)</div> |
| | Bath: | Base bath, white acrylic, 1500mm x 750mm or 1700mm x 750mm, with chrome waste and black rubber plug (Size is Product specific, refer working drawings) |
| | Shower Bases: | <div><div>Master Bedroom Ensuite, and Bathroom(s):</div></div> <div>White glass fibre composite with matching waste (Product specific, refer to working drawings for standard inclusion)</div> |
| | Shower Screens: | Semi framed with pivot (overlap) door and clear laminated glass and silver trim |
| | Taps and Outlets: | <div><div>Bath-Hob Mounted:</div><div>Bath-Wall Mounted:</div></div> <div>Posh Bristol Mk2 bath wall mixer with round backplate, lever handle and Posh Bristol Mk2 gooseneck hob swivel outlet, chrome finish (not included in all products, refer working drawings for standard inclusion) Posh Bristol Mk2 bath wall mixer with round backplate, lever handle Posh Solus 220 mm long straight wall mounted fixed outlet, chrome finish (not included in all products, refer working drawings for standard inclusion)</div> |
| | | <div><div>Shower:</div></div> <div>Posh Bristol Mk2 shower wall mixer with round backplate, lever handle and Base 1F shower head on slide rail, chrome finish</div> |
| | Basin-Top Mounted: | Posh Bristol Mk2 basin mixer with lever handle, chrome finish |
| | Basin-Wall Mounted: | Posh Bristol Mk2 basin mixer with lever handle, chrome finish (not included in all products, refer working drawings for standard inclusion) |
| | Toilet Suite: | Base Link toilet suite # 9503292, white vitreous china toilet pan with white acrylic cistern and seat, and chrome mini cistern stop tap |
| | Cabinetry: | <div><div>General:</div><div>Base Cupboards:</div><div>Doors/Drawers:</div><div>Bench Tops:</div><div>Bench Top Edges:</div><div>Handles:</div></div> <div>Refer Internal Colour scheme for finish Fully lined modular cabinets (Refer working drawings for extent) Standard laminate, from builder's Category 1 Standard laminate from builder's Category 1 Laminated square edge From builder's Category 1 (Refer to Colour scheme)</div> |

| | | | |
|--|--------------------------|---|--|
| BATHROOM/ENSUITE OR POWDER ROOM continued: | Wet Area Accessories: | Ensuites and bathroom: | Base Double Towel Rail 800mm (9503331) or Base Single Towel Rail 800mm (9503330) or Base Towel Ring (9503328) (Product specific, refer working drawings for quantity/inclusion) |
| | | Powder Room/s: | Base Towel Ring (9503328) |
| | | Toilets: | Base Toilet Roll Holder (9503325) All wet area accessories chrome finish |
| LAUNDRY: | Trough and Cabinet: | Base # 9504719, 43 litre single bowl stainless steel, with concealed bypass, standard waste, white finish metal cabinet under (Product specific) | |
| | | Skinny Mini Compact Trough and Cabinet, with concealed bypass (Product specific) | |
| | Tapware: | Trough: | Posh Bristol Mk2 upswept sink mixer with lever handle, chrome finish |
| | | Washing Machine: | Mini stop taps located inside laundry cupboard |
| | Suds By-pass: | Direct connection to side of trough waste outlet | |
| HEATING: | ** Wall Panel Heater: | Electric wall panel heaters to all bedrooms | |
| COOLING: | ** Split System: | Rinnai D-Series split system to main Living area – remote phone app for control worldwide | |
| ELECTRICAL: | Supply: | Single phase | |
| | Power Points: | 2no doubles to habitable rooms, 3no doubles to Bedroom1 and Living. Doubles to bathrooms and ensuites. | |
| | Internal Light points: | ** LED Downlights (refer to working drawings) LED step lights to staircase LED linear light to garage | |
| | External Light Points: | LED downlight to Portico/Entry (refer to working drawings) Weatherproof single flood light/s (Product specific refer working drawings) | |
| | Switch Plates: | White (wall mounted where practical). | |
| | Smoke Detector: | Hardwired, Interconnected with battery backup | |
| | Exhaust Fans: | Above all showers, also to water closets without direct ventilation to outside air | |
| | TV Point: | ** Two points (refer to working drawings) (Where Second living/TV space is applicable – additional 1No TV point will be provided) ** TV antenna removed from the project | |
| | Telephone Point (Data): | ** Two points with wall plate run to Premium Opticom location (refer working drawings) | |
| | Safety Switch: | RCD safety switch and circuit breakers to meter box | |
| | ** Switchboard: | Internal flush mounted switchboard | |
| CERAMIC TILING: | General: | Refer Internal Colour scheme for finish | |
| | Wall Tiles and Bath Hob: | Builder's Category TC 1.01 range wall tiles to areas as per standard working drawing. Plain aluminium 'L-Shape' angle trim to bath hob/riser junction | |
| | Kitchen Splashback: | Builder's Category TC 1.01 range wall tiles to areas as per standard working | |
| | Floor Tiles: | Builder's Category TC1.01 range floor tiles to laundry, bathroom, ensuite, powder room and water closets as per standard working drawing. Aluminium metal trim to doorways/openings abutting alternative floor covering. | |
| | Skirting Tiles: | 100mm high, from Builder's Category TC1.01 range floor tiles to laundry, bathroom, ensuite, powder room and water closets as per standard working drawing. | |
| | Balcony Tiles: | Glazed Ceramic tiles with textured finish to top surface from builder's Category TC 1.01 (Product specific, refer working drawings for inclusion of balcony) | |

| | | | | | |
|------------------------------------|---|--|---|--|--|
| FLOOR COVERING: | General: | Refer Internal Colour scheme for finish | | | |
| | Carpet: | Generally to the bedrooms and adjacent passage and stairs. | | | |
| | Laminate Timber look Flooring: | Generally to the entry, adjacent passage, living, meals and kitchen. | | | |
| PAVING: | General: | Subject to Developer/Town Planning requirements | | | |
| | Colour-though concrete paving: | 100mm Thick, Colour pre-selected from builder's standard range. (House/Product specific, refer working drawings for extent of paving) | | | |
| | Colour-though concrete pad: | Under clothesline (House/Product specific, refer working drawings for extent of paving) | | | |
| LANDSCAPING: | General: | Subject to Developer/Town Planning requirements Soft Landscaping (House/Product specific, refer working drawings for extent) | | | |
| | Letterbox: | Freestanding lockable Letterbox with render-style textured finish and stainless steel front panel with paperholder 75mm Stainless steel numerals | | | |
| CLOTHESLINE: | Coopers - City Living Fold Down Mainline single frame Wall Mount, with optional 'Post Kit' as required. (Inclusion and/or clothesline model Site Specific due to space limitations. Refer working drawings for location/inclusion of clothesline) | | | | |
| FENCING: | General: | Subject to Developer/Town Planning requirements Treated pine timber paling fencing. (refer Site Plan/Working Drawings for extent of fencing) | | | |
| | Dividing Boundaries: | ** 1900mm high Treated pine timber paling fencing | | | |
| | Side Boundaries: | ** 1900mm high Treated pine timber paling fencing with exposed posts and capping | | | |
| | Rear Boundary: | ** 1900mm high Treated pine timber paling fencing with exposed posts and capping | | | |
| | Wing Fence: | 1900mm high Treated pine timber paling fencing between house and side boundary including single paling gate with latch on metal frame (House/Product specific, refer working drawings for inclusion) | | | |
| | ** Front Boundaries: | 1000mm high powdercoated aluminium pool type front fencing to Lot 2405-2408, Lot 2418-2428, Lot 2430,2432,2434 & 2436 | | | |
| STORAGE: (Product specific) | Shelving: | Robes: | One white melamine shelf and hanging rail | | |
| | | Walk in Robe: | One white melamine shelf and hanging rail | | |
| | | Pantry/Linen: | Four white melamine shelves with supporting front rail (refer working drawings for inclusion) | | |
| | | Broom: | One white melamine shelf with supporting front rail (refer working drawings for inclusion) | | |
| | Doors: | General: | Sliding: | Refer Internal Colour scheme for finish 2065mm (nominal) high, aluminium frame and vinyl clad panel. (refer working drawings for extent) | |
| | | | | Hinged: | Flush panel, 2040mm high hinged door(s) (Product specific, refer working drawings) |
| | | Walk in Robe: | No Doors: | Open shelving only where no doors are indicated on working drawings. (Refer working drawings for standard inclusion) | |
| | | | With Doors: | Vinyl sliding doors or hinged doors as for 'Doors, Robes' above refer internal Colour scheme for finish. (refer working drawings for extent) | |
| | | Pantry, Linen, Broom: | Flush panel, 2040mm high hinged door(s) | | |
| | Handles: | D Pull Joinery handles | | | |
| STAIRS (Double Storey Homes only): | | MDF treads and risers, MDF closed stringer with gloss painted finish standard with timber framed and plaster balustrade. KDHW handrail, clear polyurethane finish, 14mm diameter factory finished matt black etch paint metal balusters, timber newel posts, gloss paint finished (Product specific. Refer to working drawings and Internal Colour scheme for finish) | | | |

| | | | |
|-------------------------|--|--|--|
| GARAGE: | General: | Colorbond flat metal roof, plaster ceiling, concrete floor Cladding above vehicular door opening: Brick infills, Rendered Hebel® aerated concrete infills, Lightweight Cladding infills. (Product specific, refer working drawings for type/extent) | |
| | External Walls: | Brick veneer, Single skin brickwork with attached piers, Rendered Hebel® aerated concrete, Lightweight Cladding (Product specific, refer working drawings for type/extent) | |
| | Vehicular Door: (Product specific) | Colorbond sectional overhead manual operation door with electric powered remote control unit to front garage door(s) with hand held transmitters (Refer working drawing for width of door) | |
| | Pedestrian Door: (Product specific) | Door Frame: | Timber with aluminium sill |
| | | Door: | 2040mm high weatherproof, opening in |
| CONCRETE SLAB: | | Door Furniture: | Canterbury Zenith Entry Knobset entry set |
| | | Regional North and Gippsland: | Lockwood Symmetry Manor Knobset entry set |
| | Internal Access Door: (Product specific) | Door Frame: | Timber |
| | | Door: | Weatherproof flush panel, opening into house |
| | | Door Furniture: | Canterbury Zenith Entry Knobset entry set |
| CONNECTION OF SERVICES: | | Regional North and Gippsland: | Lockwood Symmetry Manor Knobset entry set |
| | Concrete slab shall be constructed in accordance with AS 2870-2011 and in accordance with Engineers design | | |
| | House: | Slab Type: | Waffle Slab |
| | | Classification of Soil: | ** Class 'H2' |
| | Sewer Drains: | 100mm diameter Sewer grade PVC; up to 6 lineal metres of drains from residence to legal point of discharge. Includes connection of sewer point up to 1500mm deep below natural ground level. | |
| | Storm Water Drains: | 100mm diameter Stormwater grade PVC; up to 6 lineal metres of drains from residence to legal point of discharge. | |
| | Power Supply: | Single phase underground power connection from supply authority power pit at front of property to house meter box; includes up to 12 lineal metres of service line. | |
| | Communications: | ** Underground Conduit from Boundary to house, includes connection of Premium Opticom. | |
| | Water Tapping: (Dry Water Tapping) | Positioning of a 'Dry Water Tapping' in the nature strip, on the same side of the road as the property, is conditional to the point of connection as directed by the water authority. If tapping is positioned in front of a garage as a result of the house / garage siting, all associated fees, costs and works to relocate the water meter is the owner's responsibility. (Product/Design Specific) | |
| | ** Recycled Water: | Connection to recycled water infrastructure provided on site | |
| TERMITE TREATMENT: | Cold Water Supply: | Up to 6 lineal metres of 20mm diameter cold water service pipe lead-in from supply authority meter position to house external wall. | |
| | Gas Reticulation: | Up to 20 lineal metres of 32mm diameter gas service pipe from supply authority reticulation to gas meter position. | |
| | | Termite management system for concrete monolithic/raft slab. Chemically impregnated slab and brick pier perimeter barrier and chemically impregnated collars to slab penetrations | |
| WIND SPEED REQUIREMENT: | | The standard home is designed to withstand up to, and including, Wind Classification 'N2' with a maximum wind gust speed of 33m/s, in accordance with AS4055-2012 and AS1684.2-20 | |

To find out more, please speak with a Rathdowne Sales Consultant.